



Technical Data Sheet

SC2000 CEMENT

TDS #: RTTNA – 033

Rev. # 1

Rev. Date: 1/14/2014

PRODUCT NUMBERS: 101 000 041, 101 000 042, 101 000 043

CONTAINERS/PACKAGING: 101 000 041 - ½ KG Can
101 000 042 - 1 KG Can
101 000 043 – 5 KG Can

FIELD OF APPLICATION: Rema's SC2000 Cement is applicable for durable rubber-to-metal, rubber-to-rubber, rubber-to-fabric, and fabric-to-fabric bonding in the fields of wear and corrosion protection, as well as in conveyor belt technology.

PRODUCT ADVANTAGES: Excellent contact adhesion (green tack)
Non-Flammable
Approved for use in underground applications
Optimum adhesion when used with Rema Tip Top primers and cleaning fluids
Easily processed, even at low temperatures
Provides superior bonds at room temperature when processed with Rema Hardener UT-R 20
Long shelf life when stored as recommended
Available in Black and white colors

PHYSICAL PROPERTIES: Flash Point = > 200° F (> 93° C) Tag Closed Cup
Density = 12.1 Lbs./Gallon (Typical)
Boiling Point = Approximately 194° F (93° C)
Relative Vapor Density = 4.54 (Air = 1)
Solids Content = 14.0 – 19.0 (Typical)
Viscosity = 2000 – 3600 cps @ 70° F (21° C) (Typical)
VOC Content = 11.0 Lbs./Gallon (Typical)

INSTRUCTIONS FOR USE: Per the manufacturer's instructions. Rema Tip Top will provide detailed instruction for your intended use upon request.



Technical Data Sheet

SC2000 CEMENT

TDS #: RTTNA – 033

Rev. # 1

Rev. Date: 1/14/2014

SAFETY INSTRUCTIONS: Skin and eye irritant.
May cause cancer.
May cause damage to Central Nervous System, Liver, and Kidneys
May cause damage to organs with prolonged or repeated exposure
Use only in a well-ventilated area.
See Safety Data Sheets for more detailed hazards and prevention measures.

SHELF LIFE: 4 Years from Date of Manufacture in unopened original container.

BASE SOLVENT: Trichloroethylene (CAS# 79-01-6)

**RECOMMENDED STORAGE
CONDITIONS:**

Store in a cool, well-ventilated, dry environment.
Keep away from open flames, ignition sources, and incompatible materials (See Safety Data Sheet for details).
Keep container tightly closed.
Keep away from food, drink, and animal foodstuffs.

NOTICE: REMA TIP TOP / NORTH AMERICA believes that the information contained on this data sheet is accurate. It is based on extensive tests and represents standard values. However, it may not contain information on all confirmed properties. REMA TIP TOP / North America reserves the right to carry out improvements and technical development to this product at its discretion. For detailed application instructions, always refer to the appropriate Rema Tip Top Instruction Manuals and/or Repair Instruction CD's. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with nor followed in violation of applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.